

CONCRETE DELIVERY HOSES WITH HEAVY DUTY (HD) ENDS



STEEL WIRE-REINFORCED CONCRETE HOSE | 85 BAR (1235 PSI)

ID inch	OD mm	OD inch	WP PSI	BP PSI	WEIGHT lbs/ft	F.W.C. lbs/ft	BR/r inch	BR/r mm
2"	70	2.76	1232	2900	2.04	5.31	7.9	200
2½"	88	3.46	1232	2900	3.01	8.13	9.4	240
3"	102	4.02	1232	2900	3.67	11.03	10.8	275
3½"	118	4.65	1232	2900	4.91	14.90	13.7	350
4"	130	5.12	1232	2900	5.69	18.80	15.3	390
5"	155	6.10	1232	2900	6.47	26.90	16.7	425
6"	180	7.09	1232	2900	7.39	36.90	25.5	650



TUBE | Abrasion-resistant antistatic natural and CBR rubber

REINFORCEMENT | High tensile strength steel cords

COVER | Abrasion, ozone and weather-resistant pin-pricked special synthetic rubber

APPLICATION | High pressure concrete pumping and placing

COMPANY LOGO, SIZE, WEIGHT AND WORKING PRESSURE EMBOSSED ON THE OUTSIDE OF ALL HOSES.



FABRIC-REINFORCED CONCRETE HOSE

ID inch	OD mm	OD inch	WP PSI	BP PSI	WEIGHT lbs/ft	F.W.C. lbs/ft	BR/r inch	BR/r mm
1¼"	48	1.89	800	2400	0.77	2.05	7.8	200
1½"	58	2.28	800	2400	1.07	3.00	8.8	225
2"	70	2.76	800	2400	1.43	4.70	11.8	300
2½"	84	3.31	800	2400	1.73	6.85	14.7	375
3"	102	4.02	666	2000	2.72	10.08	17.7	450
4"	130	5.12	666	2000	3.96	17.07	23.6	600
4½"	142	5.59	666	2000	4.18	20.76	26.3	670
5"	155	6.10	500	1400	4.66	25.15	29.5	750



TUBE | Abrasion-resistant antistatic natural rubber

REINFORCEMENT | High tensile synthetic textile and antistatic cooper wire

COVER | Abrasion, ozone and weather-resistant pin-pricked special synthetic rubber

APPLICATION | High pressure spraying plaster, grout, sand, gypsum, ready mixed concrete

COMPANY LOGO, SIZE, WEIGHT AND WORKING PRESSURE EMBOSSED ON THE OUTSIDE OF ALL HOSES.

Putzmeister Pipe Technology
1733 90th Street
Sturtevant, WI 53177 USA
Phone: (866) 734-0296
Fax: (866) 644-1527
PutzmeisterAmerica.com

